



Prokuplje, Dragoljuba Rakića 7a
 +381 27 321 177; +381 27 334 310
 Tekući račun: 325-950080000702-77

kontakt@abmelektro.com
www.abmelektro.com
 PIB: 100 415 391



RADE KONČAR KONTAKTORI I RELEI D.O.O.



Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC 3	Broj pomoćnih kontakata 	Dimenzije a x b x c	Težina	MOTORNI KONTAKTORI, naizmjenični napon upravljanja	Cena
(A)	(kW)	ukl/iskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
20	3,0	1 0 0 1	45x48x57	0,17	CM1 10	1361
25	4,5	0 0	45x71x72,2	0,25	CNN 9 00	1420
		1 0 0 1			CNN 9 10	1455
25	4,5	0 0	45x71x72,2	0,25	CNN 9 004 ; CNN 9 00 22	1545
25	5,7	0 0	45x71x72,2	0,25	CNN 12 00	1556
		1 0			CNN 12 10	1620
		0 1			CNN 12 004 ; CNN 12 00 22	1730
30	7,5	1 0 0 1	45x71x72,2	0,26	CNN 18 10	1925
40	11	0 0	45x71x72,2	0,275	CNN 25 00	2500
40	15	0 0	45x71x72,2	0,290	CNN 30 00	2958
50	15	0 0	45x80x84,6	0,355	CNN 32 00	3560
50	18,5	0 0	45x80x84,6	0,355	CNN 40 00	4356
80	22	0 0	55x120x109	0,845	CNN 50 00	6185
85	30	0 0	55x120x109	0,850	CNN 60 00	7825
85	33	0 0	70x142x123	0,900	CNN 70 00	9188
90	37	0 0	70x142x123	1,280	CNN 80 00	11486
95	45	0 0	70x142x123	1,300	CNN 90 00	12985
100	55	0 0	70x142x123	1,350	CNN 100 00	13900
			Dodaci (blokovi pomoćnih kontakata)			RSD
		0 1 3 1 2 2 1 3 0 4 1 0 0 1	45x48x38	0,04	BPO (40, 31, 22, 13, 04), prednji	750
		1 1				
		1 1	40x35x38	0,03	BP2 11 (1NO+1NC), prednji	384
		1 1	55x10x46	0,05	BP5 11 (1NO+1NC), stranični	650
		1 1	55x10x46	0,03	BP3 11 (1NO+1NC), stranični	353
		2 2	40x35x38	0,04	BP4 22 (2NO+2NC), prednji	461
		4 0	40x35x38	0,04	* BP4 40 (4NO+0NC), prednji	461
		2 2	40x35x38	0,04	BP2 N 11 (1NO+1NC), prednji	650
		2 2	40x35x38	0,04	BP4 N 22 (2NO+2NC), prednji	808



Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC 3	Broj pomoćnih kontakata	Dimenzije a x b x c	Težina	MOTORNI KONTAKTORI, naizmjenični napon upravljanja	Cena
(A)	(kW)	ukl/iskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
63	22	2 2	87x114x111	1,30	CNM 45 22	7405
		4 4	112x114x111	1,40	CNM 45 44	8805
72	30	2 2	87x114x111	1,30	CNM 60 22	8918
		4 4	112x114x111	1,40	CNM 60 44	10314
100	37	2 2	100x132x142	2,27	CNM 75 22	13503
		4 4	125x132x142	2,37	CNM 75 44	14818
110	45	2 2	100x132x142	2,28	CNM 90 22	16695
		4 4	125x132x142	2,38	CNM 90 44	18158
115	55	2 2	100x132x142	2,29	CNM 110 22	17921
		4 4	125x132x142	2,39	CNM 110 44	19351
		2 2	135x180x189	5,10	CNM 140 22	27178
		4 4	135x180x189	5,60	CNM 140 44	29153
		2 2	135x180x189	5,20	CNM 170 22	30582
		4 4	162x180x189	5,70	CNM 170 44	32889
		2 2	135x180x189	5,30	CNM 200 22	37209
		4 4	162x180x189	5,80	CNM 200 44	39566
		2 2	160x200x226	8,40	CNM 250 22	50412
		4 4	187x200x226	8,90	CNM 250 44	52907
		2 2	160x200x226	8,50	CNM 315 22	62810
		4 4	187x200x226	8,90	CNM 315 44	64765
		2 2	160x200x226	8,50	CNM 400 22	75945
		4 4	187x200x226	8,90	CNM 400 44	77920
700	250	2 2	220x250x225	13,50	CNM 450 22	128125
800	315	2 2	220x250x225	14,00	CNM 550 22	164897
1000	400	2 2	280x307x291	26,40	CNM 700 22	182148
1100	500	2 2	280x307x291	27,80	CNM 860 22	254969
1200	580	2 2	334x490x345	51,00	CNM 1000 22	705769
Dodatci						
					RC elementi za CNNP ; CNN9 - CNN 40	359
				0,021	dotatci za priklucke za (CNN 32 - CNN 40) za priklucenje vodiča do 25mm ² , (2 komada),br.dela:601478	769
				0,14	Set od 6 štitičnika (poklopca) za terminale kontaktora (CNM 75-CNM110),br.dela:603311	2563
				0,15	Set od 6 štitičnika (poklopca) za terminale kontaktora (CNM 140-CNM200),br.dela:604128	3075
Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC 3	Broj pomoćnih kontakata	Dimenzije a x b x c	Težina	MOTORNI KONTAKTORI, naizmjenični napon upravljanja	Cena
(A)	(kW)	ukl/iskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
23	4,7	1 1	68x68x78,5	0,425	CN 10	3016
		2 0				
		0 2				
30	7,5	1 1	68x68x78,5	0,425	CN 16	3201
		2 0				
		0 2				
35	12	2 2	85x100x103	0,930	CN 25	7034
45	15	2 2	85x100x103	0,935	CN 40	8812
130	40	2 2	192x190x130	5,50	CN 80	26291
160	55	2 2	192x190x130	5,60	CN 110	31826
220	90	2 2	212x234x180	9,50	CN 170	57080
300	132	2 2	212x234x180	9,70	CN 250	81872



Nazivna nominalna struja Ie kod Un=230 V, AC 15/AC 14		Broj pomoćnih kontakata ↓ ↑	Dimenzije a x b x c	Težina	MOTORNI KONTAKTORI, naizmjenični napon upravljanja	Cena
(A)		ukl/iskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
6		4 0 3 1 2 2	45x48x56	0,17	CP0	1359
10		4 0 3 1 2 2 1 3 0 4	45x71x72,2	0,25	CNNP	1466
		sve izvedbe kao CNNP	45x71x72,2	0,27	CNNP F	1974
Nazivna nominalna struja Ie kod Un=400 V, AC 6b	Snaga konden. kod Un=400V, AC 6b	Broj pomoćnih kontakata ↓ ↑	Dimenzije a x b x c	Težina	Kondenzatorski kontaktori CNNK naizmjenični napon upravljanja	Cena
(A)	(kVar)	ukl/iskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
18	2,5	1 0	45x71x72,2	0,25	CNNK 2,5	1800
18	5	1 0	45x71x72,2	0,25	CNNK 5	2010
29	7,5	0 0	45x71x72,2	0,275	CNNK 7,5	2193
14	10	2 0	45x72,2x108	0,314	CNNK 10 20	2385
14	10	1 1	45x72,2x108	0,314	CNNK 10 11	2385
18	12,5	2 0	45x72,2x108	0,316	CNNK 12 20	2519
18	12,5	1 1	45x72,2x108	0,316	CNNK 12 11	2519
22	15	2 0	45x72,2x108	0,318	CNNK 15 20	2981
22	15	1 1	45x72,2x108	0,318	CNNK 15 11	2981
29	20	1 0	45x80x121,3	0,333	CNNK 20 10	3208
36	25	1 0	45x80x121,3	0,404	CNNK 25 E 10	4044
36	25	1 0	45x80x121,4	0,404	CNNK 25 10	4408
44	30	1 0	45x80x121,3	0,414	CNNK 30 10	5028
50	40	1 0	55x120x109	0,875	CNNK 40 10	6530
72	50	1 0	55x120x109	0,880	CNNK 50 10	7434
87	60	1 0	55x120x109	0,920	CNNK 60 10	8619
101	70	1 0	70x142x123	1,320	CNNK 70 10	13100
108	75	2 2	130x158x145	2	CNKM 75 22	15619
108	75	2 2	130x158x145	2,47	CNKM 80 22	19200
Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC 1	Broj pomoćnih kontakata ↓ ↑	Dimenzije a x b x c	Težina	TERMIČKI KONTAKTORI, naizmjenični napon upravljanja	Cena
(A)	(kW)	ukl/iskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
65	43	2 2	45x129x113	0,59	TKN 65 00	6174
115	76	2 2	87x172x111	1,50	TKN 115 22	10857
130	85	2 2	100x158x140	2,42	TK 130 22	18891
175	115	2 2	100x158x140	2,42	TK 175 22	20852



Nazivna nominalna struja Ie kod Un=400 V, AC 2/AC3	Nazivna nominalna snaga Pn, Un=400 V, AC 2/AC3	Broj pomoćnih kontakata ↓ ↑	Dimenzije a x b x c	Težina	Kontaktori MBCNN i MBCNM (mehanička i električna blokada)	Cena
(A)	(kW)	ukl/iskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
6,5	2,2	0 0	83x110x56	0,41	MBCM1 00	3951
6,5	2,2	1 0	83x110x56	0,41	MBCM1 10	4273
9	4,5	0 0	100x72,2x71	0,503	MBCNN 9 00	4434
9	4,5	1 1	120x72,2x71	0,505	MBCNN 9 11	5106
12	5,7	0 0	100x72,2x71	0,503	MBCNN 12 00	4918
12	5,7	1 1	120x72,2x71	0,505	MBCNN 12 11	5590
18	7,5	0 0	100x72,2x71	0,523	MBCNN 18 00	5563
18	7,5	1 1	120x72,2x71	0,525	MBCNN 18 11	6235
25	11	1 0	100x72,2x71	0,553	MBCNN 25 10	7538
30	11	1 0	100x72,2x71	0,553	MBCNN 30 10	8425
32	15	1 0	120x80x84,6	0,713	MBCNN 32 10	10078
40	18,5	1 0	120x80x84,6	0,713	MBCNN 40 10	11933
45	22	1 0	160x140x111	2,80	MBCNN 50 10	18060
45	22	2 1	160x140x111	2,80	MBCNN 50 21	19404
60	30	1 0	160x140x111	2,82	MBCNN 60 10	22575
60	30	2 1	160x140x111	2,82	MBCNN 60 21	23919
65	33	1 0	160x140x111	2,88	MBCNN 70 10	28219
65	33	2 1	160x140x111	2,88	MBCNN 70 21	29563
75	37	1 0	200x150x102	3,78	MBCNN 80 10	34266
75	37	2 1	200x150x102	3,78	MBCNN 80 21	35609
90	45	1 0	200x150x102	3,81	MBCNN 90 10	36684
90	45	2 1	200x150x102	3,81	MBCNN 90 21	38028
110	55	2 1	200x150x102	5,78	MBCNM 110 21	52003
140	75	2 1	270x210x189	14,20	MBCNM 140 21	80222
170	90	2 1	270x210x189	14,40	MBCNM 170 21	92719
200	105	2 1	270x210x189	14,60	MBCNM 200 21	108844
250	132	2 1	310x235x226	23,00	MBCNM 250 21	149156
315	160	2 1	310x235x226	23,20	MBCNM 315 21	181406
400	200	2 1	310x235x226	23,40	MBCNM 400 21	225750
Dodatci						
				0,003	MB2, mehanička blokada za CNN9-CNN40	954
					MB3, mehanička blokada za CNN50-CNN90	4166
Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC 3	Broj pomoćnih kontakata ↓ ↑	Dimenzije a x b x c	Težina	Bešumni kontaktori CNB jednosmerni napon upravljanja	Cena
(A)	(kW)	ukl/iskl	(mm)	(kg)	Standardni naponi: 24, 110, 220 DC	RSD
10	4,5	4 0	45x90x129	0,60	CNNPB	2661
		3 1				
		2 2				
		1 3				
		0 4				
					CNNPB F	3043
25	4,5	1 0			CNNB 9 10	2661
25	5,7	1 0			CNNB 12 10	2914
30	7,5	3 2			CNNB 18 10	3303
40	11	0 0			CNNB 25 00	3515
		2 2			CNNB 30 00	4107



Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC 3	Broj pomoćnih kontakata ⌋ ⌋	Dimenzije a x b x c	Težina	MOTORNI KONTAKTORI jednosmerni napon upravljanja	Cena
(A)	(kW)	ukl/iskl	(mm)	(kg)	Standardni naponi: 24, 110, 220 DC	RSD
16		4 0	45x75x85	0,37	CNNP 40 EG	2822
25	4,5	1 0	50x71x72,2	0,25	CNN 9 10	2016
25	5,7	1 0	50x71x72,2	0,25	CNN 12 10	2177
30	7,5	1 0	50x71x72,2	0,26	CNN 18 10	2392
40	11	1 0	50x71x72,2	0,275	CNN 25 10	3118
40	15	1 0	50x71x72,2	0,290	CNN 30 10	3413
50	15	1 0	50x80x84,6	0,36	CNN 32 10	3964
50	18,5	1 0	50x80x84,6	0,36	CNN 40 10	4821
85	22	1 0	60x120x109	0,85	CNN 50 10	6692
85	30	1 0	60x120x109	0,85	CNN 60 10	8197
90	33	1 0	75x142x123	0,90	CNN 70 10	10078
95	37	1 0	75x142x123	1,28	CNN 80 10	13077
105	45	1 0	75x142x123	1,30	CNN 90 10	14883
105	50	1 0	75x142x123	1,350	CNN 100 10	15856
115	55	2 1	100x132x142	2,29	CNM 110 21 (11)	19350
		4 3	125x132x142	2,39	CNM 110 43 (33)	20963
250	75	2 1	135x180x189	5,10	CNM 140 21 (12)	28084
		4 3	162x180x189	5,60	CNM 140 43 (34)	30208
250	90	2 1	135x180x189	5,20	CNM 170 21 (12)	32250
		4 3	162x180x189	5,70	CNM 170 43 (34)	34938
250	105	2 1	135x180x189	5,30	CNM 200 21 (12)	37625
		4 3	162x180x189	5,80	CNM 200 43 (34)	40313
350	132	2 1	160x200x226	8,40	CNM 250 21 (12)	52406
		4 3	187x200x226	8,90	CNM 250 43 (34)	55094
390	160	2 1	160x200x226	8,50	CNM 315 21 (12)	63156
		4 3	187x200x226	8,90	CNM 315 43 (34)	65844
450	200	2 1	160x200x226	8,50	CNM 400 21 (12)	77938
		4 3	187x200x226	8,90	CNM 400 43 (34)	80625
23	4,7	11 02 20	68x68x78,5	0,425	CN 10	4112
30	7,5	11 02 20	68x68x78,5	0,425	CN 16	4367
35	12	2 2	85x100x103	0,930	CN 25	9594
45	15	2 2	85x100x103	0,935	CN 40	12013
130	40	2 2	192x190x130	5,50	CN 80	31686
160	55	2 2	192x190x130	5,60	CN 110	38404
220	90	2 2	212x234x180	9,50	CN 170	68531
300	132	2 2	212x234x180	9,70	CN 250	98766
Nazivna nominalna struja Ie kod Un=220 V, DC3/DC5	Nazivna nominalna snaga Pn, Un=220 V, DC3/DC5	Broj pomoćnih kontakata ⌋ ⌋	Dimenzije a x b x c	Težina	KONTAKTORI za DC MOTORE jednosmerni napon upravljanja	Cena
(A)	(kW)	ukl/iskl	(mm)	(kg)	Standardni naponi: 24, 110, 220 DC	RSD
30	5	2 2	85x100x103	0,97	CNO 30 22	9689
30	5	2 2	85x100x103	0,97	CNOg 30 22	10176
80	16	2 2	192x190x130	5,70	CNO 110 22	42115
170	22	2 2	212x234x180	9,70	CNO 250 22	107599
Nazivna nominalna struja Ie kod Un=220 V, DC3/DC5	Nazivna nominalna snaga Pn, Un=220 V, DC3/DC5	Broj pomoćnih kontakata ⌋ ⌋	Dimenzije a x b x c	Težina	KONTAKTORI za DC MOTORE jednosmerni napon upravljanja	Cena
(A)	(kW)	ukl/iskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
30	5	2 2	85x100x103	0,97	CNO 30 22	9202
30	5	2 2	85x100x103	0,97	CNOg 30 22	9666
80	16	2 2	192x190x130	5,70	CNO 110 22	36467
170	22	2 2	212x234x180	9,70	CNO 250 22	93165
Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC2/AC3	Broj pomoćnih kontakata ⌋ ⌋	Dimenzije a x b x c	Težina	SKLOPNICI U KUĆIŠTU naizmjenični napon upravljanja	Cena
(A)	(kW)	ukl/iskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
25	4	1 0	100x191x123		PN 9	3288
25	5,5	2 2	100x191x123		PN 12	3834
25	7,5	2 2	100x191x123		PN 16	4446
35	11	2 2	100x191x123		PN 22	5312
39	15	2 2	100x191x123		PN 30	6652

Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC2/AC3	Broj pomoćnih kontakata y t	Dimenzije a x b x c	Težina	SKLOPNICI sa BIMETALNIM RELEJEM U KUČIŠTU naizmenični napon upravljanja	Cena
(A)	(kW)	ukl/iskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
25	4		100x191x123		PNRT 9	6762
25	5,5	1 2	100x191x123		PNRT 12	7395
25	7,5	1 2	100x191x123		PNRT 16	8010
35	11	1 2	100x191x123		PNRT 22	9397
39	15	1 2	100x191x123		PNRT 30	10737
25	4	1 0	100x191x123		PNRG 9	6368
25	5,5	2 2	100x191x123		PNRG 12	7001
25	7,5	2 2	100x191x123		PNRG 16	7613
35	11	2 2	100x191x123		PNRG 22	9000
39	15	2 2	100x191x123		PNRG 30	10342

REZERVNI DELOVI ZA KONTAKTORE

Cena (RSD)

Tip	Glavni kontakti komplet	Jedan blok pomoćnih kontakata	KALEM naizmenični napon upravljanja	KALEM jednosmerni napon	Lučna komora
CNM 36	2537	641	1009	1110	
CNM 45	3049	641	2199	2419	
CNM 60	4818	641	2199	2419	
CNM 75	6944	641	3881	4269	2858
CNM 90	8431	641	3881	4269	2858
CNM 110	9328	641	3881	4269	2858
CNM 140	12172	1025	6443	7090	7303
CNM 170	13607	1025	6443	7090	7303
CNM 200	18886	1025	6443	7090	7303
CNM 250	25266	1025	12420	13662	14658
CNM 315	35142	1025	12420	13662	14658
CNM 400	41846	1025	12420	13662	14658
CN 10	1271	999	1268	1395	
CN 16	1348	999	1268	1395	
CN 25	2281	1614	2536	2789	1361
CN 40	2783	1614	2536	2789	1547
CNO 30	3062	1614	2536	2789	2343
CN 63	5927	2588	4899	5387	2170
CNO 63	6519	2588	4899	5387	2170
CN 80	8764	2588	6968	7664	3407
CN 110	10609	2588	6968	7664	4333
CNO 110	11670	2588	6968	7664	4333
CN 170	19027	2588	13455	14801	9907
CN 250	27291	2588	13455	14801	9907
CNO 250	30020	2588	13455	14801	9907
CNB 50	6381	2588		6888	2170
TK 115	5791	1256	2199		
TK 130	8328	1256	3881		2857
TK 175	11198	1256	3881		2857
CM1			1000		
CNP 21/31			1000		
CNM 9,12,16,22,30,36			1000		
CNN 9,12,18,25			998		
CNN 32,40,50,60			1051		
CNN 70,80,90			1527		
TK 25, 35, 65			998		
CNB 9, 21, 31, 12				1854	
CNB 16, 22, 30				1944	

Napomena: - Kod izvedbi "pojačanih" kompleta glavnih kontakata, gore navedene cene se povećavaju za 30%

- Cene kalema se odnose samo na standardne napone upravljanja
- Za nestandardne napone cena je 10% veća

Pomoćni kontakti za UTKN

	RSD
CN 10/16	830
CN 25/40	895
CNM 36-110	4761
CN 63-250	4898