



Prokuplje, Dragoljuba Rakića 7a  
 +381 27 321 177; +381 27 334 310  
 Tekući račun: 325-950080000702-77

[kontakt@abmelektro.com](mailto:kontakt@abmelektro.com)  
[www.abmelektro.com](http://www.abmelektro.com)  
 PIB: 100 415 391



**RADE KONČAR** KONTAKTORI I RELEI D.O.O.



**KONDEZATORSKE BATERIJE**

OSNOVNE KARAKTERISTIKE	TIP	RSD
2,5 kVari, 440V/50Hz	RKC 440 S, 2,5 kVar	2693
5,0 kVari, 440V/50Hz	RKC 440 S, 5 kVar	3276
7,5 kVari, 440V/50Hz	RKC 440 S, 7,5 kVar	4040
10,0 kVari, 440V/50Hz	RKC 440 S, 10 kVar, HD	5040
12,5 kVari, 440V/50Hz	RKC 440 S, 12,5 kVar, HD	5835
15,0 kVari, 440V/50Hz	RKC 440 S, 15 kVar, HD	6956
20,0 kVari, 440V/50Hz	RKC 440 S, 20 kVar, HD	8153
25,0 kVari, 440V/50Hz	RKC 440 S, 25 kVar, HD	9650
30,0 kVari, 440V/50Hz	RKC 440 S, 30 kVar, HD	10847

Pojašnjenje: HD (eng. Heavy Duty) - kondenzatorske baterije za teške uslove rada

**REGULATORI**

OSNOVNE KARAKTERISTIKE	TIP	RSD
4-stepeni (jednofazni)	RKPFK 4	11222
6-stepeni (jednofazni)	RKPFK 6	14516
8-stepeni (jednofazni)	RKPFK 8	15960
12-stepeni (jednofazni)	RKPFK 12	18141
15-stepeni (trofazni)	RKPFK 15	22688

**PRIGUŠNICE**

OSNOVNE KARAKTERISTIKE	TIP	RSD
12.5 kVAr/400V 189Hz p=7% (15kVAr/440V)	ERH-7/400/12.5	22806
22.2 kVAr/400V 189Hz p=7% (25kVAr/440V)	ERH-7/400/22.2	33056
44.4 kVAr/400V 189Hz p=7% (50kVAr/440V)	ERH-7/400/44.4	45356

Nazivna nominalna struja Ie kod Un=400 V, AC 6b	Snaga kondenz. kod Un=400V, AC 6b	Broj pomoćnih kontakata	Dimenzije a x b x c	Težina	Kondenzatorski kontaktori CNNK naizmenični napon upravljanja	Cena
(A)	(kVar)	ukl/fiskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
18	2,5	1 0	45x71x72,2	0,25	CNNK 2,5	1800
18	5	1 0	45x71x72,2	0,25	CNNK 5	2010
29	7,5	0 0	45x71x72,2	0,275	CNNK 7,5	2193
14	10	2 0	45x72,2x108	0,314	CNNK 10 20	2385
14	10	1 1	45x72,2x108	0,314	CNNK 10 11	2385
18	12,5	2 0	45x72,2x108	0,316	CNNK 12 20	2519
18	12,5	1 1	45x72,2x108	0,316	CNNK 12 11	2519
22	15	2 0	45x72,2x108	0,318	CNNK 15 20	2981
22	15	1 1	45x72,2x108	0,318	CNNK 15 11	2981
29	20	1 0	45x80x121,3	0,333	CNNK 20 10	3208
36	25	1 0	45x80x121,3	0,404	CNNK 25 E 10	4044
36	25	1 0	45x80x121,4	0,404	CNNK 25 10	4408
44	30	1 0	45x80x121,3	0,414	CNNK 30 10	5028
50	40	1 0	55x120x109	0,875	CNNK 40 10	6530
72	50	1 0	55x120x109	0,880	CNNK 50 10	7434
87	60	1 0	55x120x109	0,920	CNNK 60 10	8619
101	70	1 0	70x142x123	1,320	CNNK 70 10	13100
108	75	2 2	130x158x145	2	CNNK 75 22	15619
108	75	2 2	130x158x145	2,47	CNNK 80 22	19200

