



Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC 3	Broj pomoćnih kontakata 	Dimenzije a x b x c	Težina	MOTORNI KONTAKTORI CNN, naizmenični napon upravljanja	Cena
(A)	(kW)	ukl/fiskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
20	3.0	1 0 0 1	45x48x57	0.17	CM1 10	1473
25	4.5	0 0	45x71x72,2	0.25	CNN 9 00	1537
		1 0			CNN 9 10	1575
		0 1				
25	4.5	0 0	45x71x72,2	0.25	CNN 9 004 ; CNN 9 00 22	1673
25	5.7	0 0	45x71x72,2	0.25	CNN 12 00	1684
		1 0			CNN 12 10	1754
		0 1				
25	5.7	0 0	45x71x72,2	0.25	CNN 12 004 ; CNN 12 00 22	1873
30	7.5	1 0 0 1	45x71x72,2	0.26	CNN 18 10	2084
		0 0				
40	11	0 0	45x71x72,2	0.275	CNN 25 00	2706
40	15	0 0	45x71x72,2	0.290	CNN 30 00	3202
50	15	0 0	45x80x84,6	0.355	CNN 32 00	3854
50	18,5	0 0	45x80x84,6	0.355	CNN 40 00	4716
80	22	0 0	55x120x109	0.845	CNN 50 00	6695
85	30	0 0	55x120x109	0.850	CNN 60 00	8471
85	33	0 0	70x142x123	0.900	CNN 70 00	9947
90	37	0 0	70x142x123	1.280	CNN 80 00	12434
95	45	0 0	70x142x123	1.300	CNN 90 00	14057
100	55	0 0	70x142x123	1.350	CNN 100 00	15047
					Dodaci (blokovi pomoćnih kontakata)	RSD
		0 1 3 1 2 2 1 3 0 4	45x48x38	0.04	BPO (40, 31, 22, 13, 04), prednji	812
		1 0 0 1		0.013	BP1 (1NO ili 1NC), stranični	346
		1 1	40x35x38	0.03	BP2 11 (1NO+1NC), prednji	416
		1 1	55x10x46	0.05	BP5 11 (1NO+1NC), stranični	704
		1 1	55x10x46	0.03	BP3 11 (1NO+1NC), stranični	382
		2 2	40x35x38	0.04	BP4 22 (2NO+2NC), prednji	499
		4 0	40x35x38	0.04	* BP4 40 (4NO+0NC), prednji	499
		2 2	40x35x38	0.04	BP2 N 11 (1NO+1NC), prednji	704
		2 2	40x35x38	0.04	BP4 N 22 (2NO+2NC), prednji	874





Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC 3	Broj pomoćnih kontakata Y Y	Dimenzije a x b x c	Težina	MOTORNI KONTAKTORI CNM, naizmenični napon upravljanja	Cena
(A)	(kW)	ukl/fiskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
63	22	2 2	87x114x111	1.30	CNM 45 22	8017
		4 4	112x114x111	1.40	CNM 45 44	9532
72	30	2 2	87x114x111	1.30	CNM 60 22	9654
		4 4	112x114x111	1.40	CNM 60 44	11165
100	37	2 2	100x132x142	2.27	CNM 75 22	14618
		4 4	125x132x142	2.37	CNM 75 44	16041
110	45	2 2	100x132x142	2.28	CNM 90 22	18073
		4 4	125x132x142	2.38	CNM 90 44	19657
115	55	2 2	100x132x142	2.29	CNM 110 22	19400
		4 4	125x132x142	2.39	CNM 110 44	20948
		2 2	135x180x189	5.10	CNM 140 22	29422
		4 4	135x180x189	5.60	CNM 140 44	31560
		2 2	135x180x189	5.20	CNM 170 22	33106
		4 4	162x180x189	5.70	CNM 170 44	35604
		2 2	135x180x189	5.30	CNM 200 22	40281
		4 4	162x180x189	5.80	CNM 200 44	42832
		2 2	160x200x226	8.40	CNM 250 22	54574
		4 4	187x200x226	8.90	CNM 250 44	57275
		2 2	160x200x226	8.50	CNM 315 22	67995
		4 4	187x200x226	8.90	CNM 315 44	70112
		2 2	160x200x226	8.50	CNM 400 22	82214
		4 4	187x200x226	8.90	CNM 400 44	84352
700	250	2 2	220x250x225	13.50	CNM 450 22	134531
800	315	2 2	220x250x225	14.00	CNM 550 22	173142
1000	400	2 2	280x307x291	26.40	CNM 700 22	191255
1100	500	2 2	280x307x291	27.80	CNM 860 22	267717
1200	580	2 2	334x490x345	51.00	CNM 1000 22	741057
		Težina(kg)	Dodatci			
			RC elementi za CNNP ; CNN9 - CNN 40			388
		0.021	dodatci za priključke za (CNN 32 - CNN 40) za priključenje vodiča do 25mm ² , (2 komada),br.dela:601478			832
		0.14	Set od 6 štitnika (poklopca) za terminale kontakatora (CNM 75-CNM110),br.dela:603311			2774
		0.15	Set od 6 štitnika (poklopca) za terminale kontakatora (CNM 140-CNM200),br.dela:604128			3329
Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC 3	Broj pomoćnih kontakata Y Y	Dimenzije a x b x c	Težina	MOTORNI KONTAKTORI CN, naizmenični napon upravljanja	Cena
(A)	(kW)	ukl/fiskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
23	4.7	1 1	68x68x78,5	0.425	CN 10	3325
		2 0				
		0 2				
30	7.5	1 1	68x68x78,5	0.425	CN 16	3529
		2 0				
		0 2				
35	12	2 2	85x100x103	0.930	CN 25	7755
45	15	2 2	85x100x103	0.935	CN 40	9716
130	40	2 2	192x190x130	5.50	CN 80	28298
160	55	2 2	192x190x130	5.60	CN 110	33847
220	90	2 2	212x234x180	9.50	CN 170	61016
300	132	2 2	212x234x180	9.70	CN 250	86100



Nazivna nominalna struja Ie kod Un=400 V, AC 6b	Snaga konden. kod Un=400V, AC 6b	Broj pomoćnih kontakata	Dimenzije a x b x c	Težina	Kondenzatorski kontaktori CNNK, naizmenični napon upravljanja	Cena
(A)	(kVar)	ukl/iskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
18	2.5	1 0	45x71x72,2	0.25	CNNK 2,5	1949
18	5	1 0	45x71x72,2	0.25	CNNK 5	2176
29	7.5	0 0	45x71x72,2	0.275	CNNK 7,5	2373
14	10	2 0	45x72,2x108	0.314	CNNK 10 20	2582
14	10	1 1	45x72,2x108	0.314	CNNK 10 11	2582
18	12.5	2 0	45x72,2x108	0.316	CNNK 12 20	2727
18	12.5	1 1	45x72,2x108	0.316	CNNK 12 11	2727
22	15	2 0	45x72,2x108	0.318	CNNK 15 20	3227
22	15	1 1	45x72,2x108	0.318	CNNK 15 11	3227
29	20	1 0	45x80x121,3	0.333	CNNK 20 10	3472
36	25	1 0	45x80x121,3	0.404	CNNK 25 E 10	4378
36	25	1 0	45x80x121,4	0.404	CNNK 25 10	4771
44	30	1 0	45x80x121,3	0.414	CNNK 30 10	5443
50	40	1 0	55x120x109	0.875	CNNK 40 10	7069
72	50	1 0	55x120x109	0.880	CNNK 50 10	8047
87	60	1 0	55x120x109	0.920	CNNK 60 10	9330
101	70	1 0	70x142x123	1.320	CNNK 70 10	14181
108	75	2 2	130x158x145	2	CNKM 75 22	16908
108	75	2 2	130x158x145	2.47	CNKM 80 22	20785
Nazivna nominalna struja Ie kod Un=230 V, AC 15/AC 14		Broj pomoćnih kontakata	Dimenzije a x b x c	Težina	POMOĆNI KONTAKTORI, naizmenični napon upravljanja	Cena
(A)		ukl/iskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
6		4 0	45x48x56	0.17	CP0	1471
		3 1				
		2 2				
10		4 0	45x71x72,2	0.25	CNNP	1587
		3 1				
		2 2				
		1 3				
		0 4				
		sve izvedbe kao CNNP	45x71x72,2	0.27	CNNP F	2137
Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC 1	Broj pomoćnih kontakata	Dimenzije a x b x c	Težina	TERMIČKI KONTAKTORI, naizmenični napon upravljanja	Cena
(A)	(kW)	ukl/iskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
65	43	2 2	45x129x113	0.59	TKN 65 00	6483
115	76	2 2	87x172x111	1.50	TKN 115 22	11400
130	85	2 2	100x158x140	2.42	TK 130 22	19835
175	115	2 2	100x158x140	2.42	TK 175 22	21895



Nazivna nominalna struja Ie kod Un=400 V, AC 2/AC3	Nazivna nominalna snaga Pn, Un=400 V, AC 2/AC3	Broj pomoćnih kontakata 	Dimenzije a x b x c	Težina	Kontaktori MBCNN i MBCNM (mehanička i električna blokada)	Cena
(A)	(kW)	ukl/fiskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
6.5	2.2	0 0	83x110x56	0.41	MBCM1 00	4148
6.5	2.2	1 0	83x110x56	0.41	MBCM1 10	4487
9	4.5	0 0	100x72,2x71	0.503	MBCNN 9 00	4656
9	4.5	1 1	120x72,2x71	0.505	MBCNN 9 11	5362
12	5.7	0 0	100x72,2x71	0.503	MBCNN 12 00	5164
12	5.7	1 1	120x72,2x71	0.505	MBCNN 12 11	5870
18	7.5	0 0	100x72,2x71	0.523	MBCNN 18 00	5841
18	7.5	1 1	120x72,2x71	0.525	MBCNN 18 11	6547
25	11	1 0	100x72,2x71	0.553	MBCNN 25 10	7915
30	11	1 0	100x72,2x71	0.553	MBCNN 30 10	8847
32	15	1 0	120x80x84,6	0.713	MBCNN 32 10	10582
40	18.5	1 0	120x80x84,6	0.713	MBCNN 40 10	12529
45	22	1 0	160x140x111	2.80	MBCNN 50 10	18963
45	22	2 1	160x140x111	2.80	MBCNN 50 21	20374
60	30	1 0	160x140x111	2.82	MBCNN 60 10	23704
60	30	2 1	160x140x111	2.82	MBCNN 60 21	25115
65	33	1 0	160x140x111	2.88	MBCNN 70 10	29630
65	33	2 1	160x140x111	2.88	MBCNN 70 21	31041
75	37	1 0	200x150x102	3.78	MBCNN 80 10	35979
75	37	2 1	200x150x102	3.78	MBCNN 80 21	37390
90	45	1 0	200x150x102	3.81	MBCNN 90 10	38519
90	45	2 1	200x150x102	3.81	MBCNN 90 21	39930
110	55	2 1	200x150x102	5.78	MBCNM 110 21	54603
140	75	2 1	270x210x189	14.20	MBCNM 140 21	84233
170	90	2 1	270x210x189	14.40	MBCNM 170 21	97355
200	105	2 1	270x210x189	14.60	MBCNM 200 21	114286
250	132	2 1	310x235x226	23.00	MBCNM 250 21	156614
315	160	2 1	310x235x226	23.20	MBCNM 315 21	190477
400	200	2 1	310x235x226	23.40	MBCNM 400 21	237038
Dodatci						
				0.003	MB2, mehanička blokada za CNN9-CNN4	1002
					MB3, mehanička blokada za CNN50-CNN	4374
Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC 3	Broj pomoćnih kontakata 	Dimenzije a x b x c	Težina	Bežumni kontaktori CNB jednosmerni napon upravljanja	Cena
(A)	(kW)	ukl/fiskl	(mm)	(kg)	Standardni naponi: 24, 110, 220 DC	RSD
10	4.5	4 0	45x90x129	0.60	CNNPB	2880
		3 1				
		2 2			CNNPB F	3294
		1 3				
0 4						
25	4.5	1 0			CNNB 9 10	2880
25	5.7	1 0			CNNB 12 10	3154
30	7.5	3 2			CNNB 18 10	3576
40	11	0 0			CNNB 25 00	3805
		2 2			CNNB 30 00	4446



Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC 3	Broj pomoćnih kontakata ┌ ┐	Dimenzije a x b x c	Težina	MOTORNI KONTAKTORI jednosmerni napon upravljanja	Cena
(A)	(kW)	ukl/iskl	(mm)	(kg)	Standardni naponi: 24, 110, 220 DC	RSD
16		4 0	45x75x85	0.37	CNNP 40 EG	3055
25	4.5	1 0	50x71x72,2	0.25	CNN 9 10	2182
25	5.7	1 0	50x71x72,2	0.25	CNN 12 10	2357
30	7.5	1 0	50x71x72,2	0.26	CNN 18 10	2589
40	11	1 0	50x71x72,2	0.275	CNN 25 10	3375
40	15	1 0	50x71x72,2	0.290	CNN 30 10	3695
50	15	1 0	50x80x84,6	0.36	CNN 32 10	4291
50	18.5	1 0	50x80x84,6	0.36	CNN 40 10	5219
85	22	1 0	60x120x109	0.85	CNN 50 10	7244
85	30	1 0	60x120x109	0.85	CNN 60 10	8874
90	33	1 0	75x142x123	0.90	CNN 70 10	10910
95	37	1 0	75x142x123	1.28	CNN 80 10	14157
105	45	1 0	75x142x123	1.30	CNN 90 10	16112
105	50	1 0	75x142x123	1.350	CNN 100 10	17165
115	55	2 1	100x132x142	2.29	CNM 110 21 (11)	20947
		4 3	125x132x142	2.39	CNM 110 43 (33)	22693
250	75	2 1	135x180x189	5.10	CNM 140 21 (12)	30403
		4 3	162x180x189	5.60	CNM 140 43 (34)	32701
250	90	2 1	135x180x189	5.20	CNM 170 21 (12)	34912
		4 3	162x180x189	5.70	CNM 170 43 (34)	37822
250	105	2 1	135x180x189	5.30	CNM 200 21 (12)	40731
		4 3	162x180x189	5.80	CNM 200 43 (34)	43640
350	132	2 1	160x200x226	8.40	CNM 250 21 (12)	56732
		4 3	187x200x226	8.90	CNM 250 43 (34)	59642
390	160	2 1	160x200x226	8.50	CNM 315 21 (12)	68370
		4 3	187x200x226	8.90	CNM 315 43 (34)	71279
450	200	2 1	160x200x226	8.50	CNM 400 21 (12)	84371
		4 3	187x200x226	8.90	CNM 400 43 (34)	87281
23	4.7	11 02 20	68x68x78,5	0.425	CN 10	4451
30	7.5	11 02 20	68x68x78,5	0.425	CN 16	4728
35	12	2 2	85x100x103	0.930	CN 25	10386
45	15	2 2	85x100x103	0.935	CN 40	13005
130	40	2 2	192x190x130	5.50	CN 80	34301
160	55	2 2	192x190x130	5.60	CN 110	41575
220	90	2 2	212x234x180	9.50	CN 170	74189
300	132	2 2	212x234x180	9.70	CN 250	106919
SKLOPNICI U KUĆIŠTU naizmjenični napon upravljanja						Cena
25	4	1 0	100x191x123		PN 9	3559
25	5.5	2 2	100x191x123		PN 12	4150
25	7.5	2 2	100x191x123		PN 16	4813
35	11	2 2	100x191x123		PN 22	5751
39	15	2 2	100x191x123		PN 30	7201

Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC2/AC3	Broj pomoćnih kontakata ┌ ┐	Dimenzije a x b x c	Težina	SKLOPNICI sa BIMETALNIM RELEJEM U KUĆIŠTU naizmjenični napon upravljanja	Cena
(A)	(kW)	ukl/iskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
25	4		100x191x123		PNRT 9	7321
25	5.5	1 2	100x191x123		PNRT 12	8006
25	7.5	1 2	100x191x123		PNRT 16	8672
35	11	1 2	100x191x123		PNRT 22	10172
39	15	1 2	100x191x123		PNRT 30	11623
25	4	1 0	100x191x123		PNRG 9	6893
25	5.5	2 2	100x191x123		PNRG 12	7579
25	7.5	2 2	100x191x123		PNRG 16	8242
35	11	2 2	100x191x123		PNRG 22	9742
39	15	2 2	100x191x123		PNRG 30	11196

REZERVNI DELOVI ZA KONTAKTORE					
Cena (RSD)					
Tip	Glavni kontakti komplet	Jedan blok pomoćnih kontakata	KALEM naizmjenični napon upravljanja	KALEM jednosmerni napon	Lučna komora
CNM 36	2752	695	1095	1204	
CNM 45	3308	695	2386	2624	
CNM 60	5225	695	2386	2624	
CNM 75	7532	695	4210	4631	3100
CNM 90	9144	695	4210	4631	3100
CNM 110	10117	695	4210	4631	3100
CNM 140	13202	1112	6988	7690	7921
CNM 170	14759	1112	6988	7690	7921
CNM 200	20484	1112	6988	7690	7921
CNM 250	27405	1112	13471	14818	15898
CNM 315	38117	1112	13471	14818	15898
CNM 400	45388	1112	13471	14818	15898
CN 10	1379	1084	1375	1513	
CN 16	1462	1084	1375	1513	
CN 25	2474	1751	2750	3025	1476
CN 40	3018	1751	2750	3025	1678
CNO 30	3321	1751	2750	3025	2541
CN 63	6429	2807	5314	5843	2354
CNO 63	7071	2807	5314	5843	2354
CN 80	9506	2807	7558	8313	3695
CN 110	11507	2807	7558	8313	4700
CNO 110	12657	2807	7558	8313	4700
CN 170	20637	2807	14594	16053	10745
CN 250	29601	2807	14594	16053	10745
CNO 250	32561	2807	14594	16053	10745
CNB 50	6921	2807		7471	2354
TK 115	6281	1362	2386		
TK 130	9033	1362	4210		3099
TK 175	12146	1362	4210		3099
CM1			1084		
CNP 21/31			1084		
CNM 9,12,16,22,30,36			1084		
CNN 9,12,18,25			1083		
CNN 32,40,50,60			1140		
CNN 70,80,90			1656		
TK 25, 35, 65			1083		
CNB 9, 21, 31, 12				2011	
CNB 16, 22, 30				2109	
- Kod izvedbi "pojačanih" kompleta glavnih kontakata, gore navedene cene se povećavaju za 30%					
- Cene kalema se odnose samo na standardne napone upravljanja					
- Za nestandardne napone cena je 10% veća					
Pomoćni kontakti za UTKN					RSD
CN 10/16					898
CN 25/40					969
CNM 36-110					5154
CN 63-250					5302