



Prokuplje, Dragoljuba Rakića 7a
+381 27 321 177; +381 27 334 310
Tekući račun: 325-950080000702-77

kontakt@abmelektro.com
www.abmelektro.com
PIB: 100 415 391



RADE KONČAR KONTAKTORI I RELEI D.O.O.



REGULATORI FAKTORA SNAGE

OSNOVNE KARAKTERISTIKE		TIP	RSD
4-stepeni (jednofazni)		RKPFK 4	11543
6-stepeni (jednofazni)		RKPFK 6	14931
8-stepeni (jednofazni)		RKPFK 8	16416
12-stepeni (jednofazni)		RKPFK 12	18660
15-stepeni (trofazni)		RKPFK 15	23336

PRIGUŠNICE

OSNOVNE KARAKTERISTIKE	TIP	RSD
12.5 kVar/400V 189Hz p=7% (15kVar/440V)	ERH-7/400/12.5	20425
22.2 kVar/400V 189Hz p=7% (25kVar/440V)	ERH-7/400/22.2	29605
44.4 kVar/400V 189Hz p=7% (50kVar/440V)	ERH-7/400/44.4	45356

Nazivna nominalna struja Ie kod Un=400 V, AC 6b	Snaga konden. kod Un=400V, AC 6b	Broj pomoćnih kontakata	Dimenzije a x b x c	Težina	Kondenzatorski kontaktori CNNK naizmenični napon upravljanja	Cena
(A)	(kVar)	ukl/iskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
18	2.5	1 0	45x71x72,2	0.25	CNNK 2,5	2046
18	5	1 0	45x71x72,2	0.25	CNNK 5	2285
29	7.5	0 0	45x71x72,2	0.275	CNNK 7,5	2492
14	10	2 0	45x72,2x108	0.314	CNNK 10 20	3161
14	10	1 1	45x72,2x108	0.314	CNNK 10 11	3161
18	12.5	2 0	45x72,2x108	0.316	CNNK 12 20	3353
18	12.5	1 1	45x72,2x108	0.316	CNNK 12 11	3353
22	15	2 0	45x72,2x108	0.318	CNNK 15 20	3800
22	15	1 1	45x72,2x108	0.318	CNNK 15 11	3800
29	20	1 0	45x80x121,3	0.333	CNNK 20 10	3991
36	25	1 0	45x80x121,3	0.404	CNNK 25 E 10	4950
36	25	1 0	45x80x121,4	0.404	CNNK 25 10	5271
44	30	1 0	45x80x121,3	0.414	CNNK 30 10	5718
50	40	1 0	55x120x109	0.875	CNNK 40 10	8145
72	50	1 0	55x120x109	0.880	CNNK 50 10	8783
87	60	1 0	55x120x109	0.920	CNNK 60 10	10060
101	70	1 0	70x142x123	1.320	CNNK 70 10	14890
108	75	2 2	130x158x145	2	CNKM 75 22	22326
108	75	2 2	130x158x145	2.47	CNKM 80 22	23155

