

Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC 3	Broj pomoćnih kontakata 1 0 0 1	Dimenzije a x b x c	Težina	MOTORNİ KONTAKTORI CNN, naizmenični napon upravljanja	Cena
(A)	(kW)	ukl/fiskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
20	3,0	1 0 0 1	45x48x57	0,17	CN1 10	1791
25	4,5	0 0	45x71x72,2	0,25	CNN 9 00	1780
		1 0			CNN 9 10	1737
		0 1				
25	4,5	0 0	45x71x72,2	0,25	CNN 9 004 ; CNN 9 00 22	1844
25	5,7	0 0	45x71x72,2	0,25	CNN 12 00	1857
		1 0			CNN 12 10	1933
		0 1				
25	5,7	0 0	45x71x72,2	0,25	CNN 12 004 ; CNN 12 00 22	2065
30	7,5	1 0 0 1	45x71x72,2	0,26	CNN 18 10	2298
40	11	0 0	45x71x72,2	0,275	CNN 25 00	2983
40	15	0 0	45x71x72,2	0,290	CNN 30 00	3530
50	15	0 0	45x80x84,6	0,355	CNN 32 00	4249
50	18,5	0 0	45x80x84,6	0,355	CNN 40 00	5199
80	22	0 0	55x120x109	0,845	CNN 50 00	7382
85	30	0 0	55x120x109	0,850	CNN 60 00	9339
85	33	0 0	70x142x123	0,900	CNN 70 00	10966
90	37	0 0	70x142x123	1,280	CNN 80 00	13708
95	45	0 0	70x142x123	1,300	CNN 90 00	15498
100	55	0 0	70x142x123	1,350	CNN 100 00	16590
		1 0 0 1			Dodaci (blokovi pomoćnih kontakata)	RSD
		0 1	45x48x38	0,04	BPO (40, 31, 22, 13, 04), prednji	940
		3 1				
		2 2				
		1 3				
		0 4				
		1 0 0 1		0,013	BP1 (1NO ili 1NC), stranični	382
		1 1	40x35x38	0,03	BP2 11 (1NO+1NC), prednji	459
		1 1	55x10x46	0,05	BP5 11 (1NO+1NC), stranični	776
		1 1	55x10x46	0,03	BP3 11 (1NO+1NC), stranični	421
		2 2	40x35x38	0,04	BP4 22 (2NO+2NC), prednji	551
		4 0	40x35x38	0,04	* BP4 40 (4NO+0NC), prednji	550
		2 2	40x35x38	0,04	BP2 N 11 (1NO+1NC), prednji	776
		2 2	40x35x38	0,04	BP4 N 22 (2NO+2NC), prednji	964



Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC 3	Broj pomoćnih kontakata	Dimenzije a x b x c	Težina	MOTORNİ KONTAKTORI CNM, naizmenični napon upravljanja	Cena
(A)	(kW)	ukl/iskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
63	22	2 2	87x114x111	1,30	CNM 45 22	8838
		4 4	112x114x111	1,40	CNM 45 44	10509
72	30	2 2	87x114x111	1,30	CNM 60 22	10644
		4 4	112x114x111	1,40	CNM 60 44	12309
100	37	2 2	100x132x142	2,27	CNM 75 22	16116
		4 4	125x132x142	2,37	CNM 75 44	17685
110	45	2 2	100x132x142	2,28	CNM 90 22	19925
		4 4	125x132x142	2,38	CNM 90 44	21672
115	55	2 2	100x132x142	2,29	CNM 110 22	21389
		4 4	125x132x142	2,39	CNM 110 44	23095
160	75	2 2	135x180x189	5,10	CNM 140 22	32437
		4 4	135x180x189	5,60	CNM 140 44	34795
200	90	2 2	135x180x189	5,20	CNM 170 22	36500
		4 4	162x180x189	5,70	CNM 170 44	39254
250	110	2 2	135x180x189	5,30	CNM 200 22	44409
		4 4	162x180x189	5,80	CNM 200 44	47222
300	132	2 2	160x200x226	8,40	CNM 250 22	60168
		4 4	187x200x226	8,90	CNM 250 44	63145
390	160	2 2	160x200x226	8,50	CNM 315 22	74964
		4 4	187x200x226	8,90	CNM 315 44	77298
400	200	2 2	160x200x226	8,50	CNM 400 22	90641
		4 4	187x200x226	8,90	CNM 400 44	92998
700	250	2 2	220x250x225	13,50	CNM 450 22	148321
800	315	2 2	220x250x225	14,00	CNM 550 22	190889
1000	400	2 2	280x307x291	26,40	CNM 700 22	210859
1100	500	2 2	280x307x291	27,80	CNM 860 22	295158
1200	580	2 2	334x490x345	51,00	CNM 1000 22	817016
		Težina(kg)	Dodatci			
			RC elementi za CNNP ; CNN9 - CNN 40			428
		0,021	dodatci za priključke za (CNN 32 - CNN 40) za priključenje vodiča do 25mm ² , (2 komada),br.dela:601478			918
		0,14	Set od 6 štitnika (poklopca) za terminale kontaktora (CNM 75-CNM110),br.dela:603311			3058
		0,15	Set od 6 štitnika (poklopca) za terminale kontaktora (CNM 140-CNM200),br.dela:604128			3670
Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC 3	Broj pomoćnih kontakata	Dimenzije a x b x c	Težina	MOTORNİ KONTAKTORI CN, naizmenični napon upravljanja	Cena
(A)	(kW)	ukl/iskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
23	4,7	1 1	68x68x78,5	0,425	CN 10	3666
		2 0				
		0 2				
30	7,5	1 1	68x68x78,5	0,425	CN 16	3891
		2 0				
		0 2				
35	12	2 2	85x100x103	0,930	CN 25	8550
45	15	2 2	85x100x103	0,935	CN 40	10712
130	40	2 2	192x190x130	5,50	CN 80	31198
160	55	2 2	192x190x130	5,60	CN 110	37316
220	90	2 2	212x234x180	9,50	CN 170	67270
300	132	2 2	212x234x180	9,70	CN 250	94925



Nazivna nominalna struja Ie kod Un=400 V, AC 6b	Snaga konden. kod Un=400V, AC 6b	Broj pomoćnih kontakata	Dimenzije a x b x c	Težina	Kondenzatorski kontaktori CNNK, naizmenični napon upravljanja	Cena
(A)	(kVar)	ukl/fiskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
18	2,5	1 0	45x71x72,2	0,25	CNNK 2,5	2148
18	5	1 0	45x71x72,2	0,25	CNNK 5	2399
29	7,5	0 0	45x71x72,2	0,275	CNNK 7,5	2617
14	10	2 0	45x72,2x108	0,314	CNNK 10 20	3319
14	10	1 1	45x72,2x108	0,314	CNNK 10 11	3319
18	12,5	2 0	45x72,2x108	0,316	CNNK 12 20	3520
18	12,5	1 1	45x72,2x108	0,316	CNNK 12 11	3520
22	15	2 0	45x72,2x108	0,318	CNNK 15 20	3990
22	15	1 1	45x72,2x108	0,318	CNNK 15 11	3990
29	20	1 0	45x80x121,3	0,333	CNNK 20 10	4190
36	25	1 0	45x80x121,3	0,404	CNNK 25 E 10	5198
36	25	1 0	45x80x121,4	0,404	CNNK 25 10	5534
44	30	1 0	45x80x121,3	0,414	CNNK 30 10	6004
50	40	1 0	55x120x109	0,875	CNNK 40 10	8552
72	50	1 0	55x120x109	0,880	CNNK 50 10	9223
87	60	1 0	55x120x109	0,920	CNNK 60 10	10563
101	70	1 0	70x142x123	1,320	CNNK 70 10	15635
108	75	2 2	130x158x145	2	CNKM 75 22	23442
108	75	2 2	130x158x145	2,47	CNKM 80 22	24313
Nazivna nominalna struja Ie kod Un=230 V, AC 15/AC 14		Broj pomoćnih kontakata	Dimenzije a x b x c	Težina	POMOĆNI KONTAKTORI, naizmenični napon upravljanja	Cena
(A)		ukl/fiskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
6		4 0	45x48x56	0,17	CP0	1622
		3 1				
		2 2				
10		4 0	45x71x72,2	0,25	CNNP	1750
		3 1				
		2 2				
		1 3				
	sve izvedbe kao CNNP		45x71x72,2	0,27	CNNP F	2356
Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC 1	Broj pomoćnih kontakata	Dimenzije a x b x c	Težina	TERMIČKI KONTAKTORI, naizmenični napon upravljanja	Cena
(A)	(kW)	ukl/fiskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
65	43	2 2	45x129x113	0,59	TKN 65 00	6807
115	76	2 2	87x172x111	1,50	TKN 115 22	11970
130	85	2 2	100x158x140	2,42	TK 130 22	20827
175	115	2 2	100x158x140	2,42	TK 175 22	22989



Nazivna nominalna struja Ie kod Un=400 V, AC 2/AC3	Nazivna nominalna snaga Pn, Un=400 V, AC 2/AC3	Broj pomoćnih kontakata 	Dimenzije a x b x c	Težina	Kontaktori MBCNN i MBCNM (mehanička i električna blokada)	Cena	
(A)	(kW)	ukl/iskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD	
6,5	2,2	0 0	83x110x56	0,41	MBCM1 00	4573	
6,5	2,2	1 0	83x110x56	0,41	MBCM1 10	4947	
9	4,5	0 0	100x72,2x71	0,503	MBCNN 9 00	5133	
9	4,5	1 1	120x72,2x71	0,505	MBCNN 9 11	5911	
12	5,7	0 0	100x72,2x71	0,503	MBCNN 12 00	5693	
12	5,7	1 1	120x72,2x71	0,505	MBCNN 12 11	6471	
18	7,5	0 0	100x72,2x71	0,523	MBCNN 18 00	6440	
18	7,5	1 1	120x72,2x71	0,525	MBCNN 18 11	7218	
25	11	1 0	100x72,2x71	0,553	MBCNN 25 10	8727	
30	11	1 0	100x72,2x71	0,553	MBCNN 30 10	9753	
32	15	1 0	120x80x84,6	0,713	MBCNN 32 10	11667	
40	18,5	1 0	120x80x84,6	0,713	MBCNN 40 10	13813	
45	22	1 0	160x140x111	2,80	MBCNN 50 10	20907	
45	22	2 1	160x140x111	2,80	MBCNN 50 21	22462	
60	30	1 0	160x140x111	2,82	MBCNN 60 10	26133	
60	30	2 1	160x140x111	2,82	MBCNN 60 21	27689	
65	33	1 0	160x140x111	2,88	MBCNN 70 10	32667	
65	33	2 1	160x140x111	2,88	MBCNN 70 21	34222	
75	37	1 0	200x150x102	3,78	MBCNN 80 10	39667	
75	37	2 1	200x150x102	3,78	MBCNN 80 21	41222	
90	45	1 0	200x150x102	3,81	MBCNN 90 10	42467	
90	45	2 1	200x150x102	3,81	MBCNN 90 21	44022	
110	55	2 1	200x150x102	5,78	MBCNM 110 21	60200	
140	75	2 1	270x210x189	14,20	MBCNM 140 21	92867	
170	90	2 1	270x210x189	14,40	MBCNM 170 21	107334	
200	105	2 1	270x210x189	14,60	MBCNM 200 21	126000	
250	132	2 1	310x235x226	23,00	MBCNM 250 21	172667	
315	160	2 1	310x235x226	23,20	MBCNM 315 21	210000	
400	200	2 1	310x235x226	23,40	MBCNM 400 21	261334	
Dodatci							
				0,003	MB2, mehanička blokada za CNN9-CNN40	1104	
					MB3, mehanička blokada za CNN50-CNN90	4822	
Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC 3	Broj pomoćnih kontakata 	Dimenzije a x b x c	Težina	Bešumni kontaktori CNB jednosmerni napon upravljanja	Cena	
(A)	(kW)	ukl/iskl	(mm)	(kg)	Standardni naponi: 24, 110, 220 DC	RSD	
10	4,5	4 0	45x90x129	0,60	CNNPB	3176	
		3 1					
		2 2			CNNPB F		3632
		1 3					
		0 4					
25	4,5	1 0			CNNB 9 10	3176	
25	5,7	1 0			CNNB 12 10	3478	
30	7,5	3 2			CNNB 18 10	3943	
40	11	0 0			CNNB 25 00	4195	
		2 2			CNNB 30 00	4902	



Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC 3	Broj pomoćnih kontakata 	Dimenzije a x b x c	Težina	MOTORNİ KONTAKTORI jednosmerni napon upravljanja	Cena
(A)	(kW)	ukl/iskl	(mm)	(kg)	Standardni naponi: 24, 110, 220 DC	RSD
16		4 0	45x75x85	0,37	CNNP 40 EG	3368
25	4,5	1 0	50x71x72,2	0,25	CNN 9 10	2406
25	5,7	1 0	50x71x72,2	0,25	CNN 12 10	2598
30	7,5	1 0	50x71x72,2	0,26	CNN 18 10	2855
40	11	1 0	50x71x72,2	0,275	CNN 25 10	3721
40	15	1 0	50x71x72,2	0,290	CNN 30 10	4074
50	15	1 0	50x80x84,6	0,36	CNN 32 10	4731
50	18,5	1 0	50x80x84,6	0,36	CNN 40 10	5754
85	22	1 0	60x120x109	0,85	CNN 50 10	7987
85	30	1 0	60x120x109	0,85	CNN 60 10	9783
90	33	1 0	75x142x123	0,90	CNN 70 10	12028
95	37	1 0	75x142x123	1,28	CNN 80 10	15608
105	45	1 0	75x142x123	1,30	CNN 90 10	17763
105	50	1 0	75x142x123	1,350	CNN 100 10	18925
115	55	2 1	100x132x142	2,29	CNM 110 21 (11)	23094
		4 3	125x132x142	2,39	CNM 110 43 (33)	25019
250	75	2 1	135x180x189	5,10	CNM 140 21 (12)	33519
		4 3	162x180x189	5,60	CNM 140 43 (34)	36053
250	90	2 1	135x180x189	5,20	CNM 170 21 (12)	38491
		4 3	162x180x189	5,70	CNM 170 43 (34)	41698
250	105	2 1	135x180x189	5,30	CNM 200 21 (12)	44906
		4 3	162x180x189	5,80	CNM 200 43 (34)	48113
350	132	2 1	160x200x226	8,40	CNM 250 21 (12)	62547
		4 3	187x200x226	8,90	CNM 250 43 (34)	65755
390	160	2 1	160x200x226	8,50	CNM 315 21 (12)	75378
		4 3	187x200x226	8,90	CNM 315 43 (34)	78585
450	200	2 1	160x200x226	8,50	CNM 400 21 (12)	93019
		4 3	187x200x226	8,90	CNM 400 43 (34)	96227
23	4,7	11 02 20	68x68x78,5	0,425	CN 10	4908
30	7,5	11 02 20	68x68x78,5	0,425	CN 16	5212
35	12	2 2	85x100x103	0,930	CN 25	11451
45	15	2 2	85x100x103	0,935	CN 40	14338
130	40	2 2	192x190x130	5,50	CN 80	37817
160	55	2 2	192x190x130	5,60	CN 110	45836
220	90	2 2	212x234x180	9,50	CN 170	81793
300	132	2 2	212x234x180	9,70	CN 250	117878
SKLOPNICI U KUĆIŠTU naizmjenični napon upravljanja						Cena
25	4	1 0	100x191x123		PN 9	3924
25	5,5	2 2	100x191x123		PN 12	4575
25	7,5	2 2	100x191x123		PN 16	5306
35	11	2 2	100x191x123		PN 22	6340
39	15	2 2	100x191x123		PN 30	7940

Nazivna nominalna struja Ie kod Un=400 V, AC 1	Nazivna nominalna snaga Pn, Un=400 V, AC2/AC3	Broj pomoćnih kontakata 	Dimenzije a x b x c	Težina	SKLOPNICI sa BIMETALNIM RELEJEM U KUĆIŠTU naizmjenični napon upravljanja	Cena
(A)	(kW)	ukl/iskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
25	4		100x191x123		PNRT 9	8071
25	5,5	1 2	100x191x123		PNRT 12	8826
25	7,5	1 2	100x191x123		PNRT 16	9560
35	11	1 2	100x191x123		PNRT 22	11215
39	15	1 2	100x191x123		PNRT 30	12815
25	4	1 0	100x191x123		PNRG 9	7600
25	5,5	2 2	100x191x123		PNRG 12	8355
25	7,5	2 2	100x191x123		PNRG 16	9086

35	11	2 2	100x191x123	PNRG 22	10741
39	15	2 2	100x191x123	PNRG 30	12344

REZERVNI DELOVI ZA KONTAKTORE					
Cena (RSD)					
Tip	Glavni kontakti komplet	Jedan blok pomoćnih kontakata	KALEM naizmenični napon upravljanja	KALEM jednosmerni napon	Lučna komora
CNM 36	3063	773	1218	1340	
CNM 45	3681	773	2655	2921	
CNM 60	5816	773	2655	2921	
CNM 75	8383	773	4686	5154	3451
CNM 90	10178	773	4686	5154	3451
CNM 110	11260	773	4686	5154	3451
CNM 140	14694	1237	7778	8559	8816
CNM 170	16426	1237	7778	8559	8816
CNM 200	22799	1237	7778	8559	8816
CNM 250	30502	1237	14994	16493	17695
CNM 315	42424	1237	14994	16493	17695
CNM 400	50517	1237	14994	16493	17695
CN 10	1534	1206	1531	1684	
CN 16	1627	1206	1531	1684	
CN 25	2753	1949	3061	3367	1643
CN 40	3360	1949	3061	3367	1867
CNO 30	3697	1949	3061	3367	2828
CN 63	7155	3124	5914	6503	2620
CNO 63	7870	3124	5914	6503	2620
CN 80	10580	3124	8412	9252	4113
CN 110	12807	3124	8412	9252	5231
CNO 110	14088	3124	8412	9252	5231
CN 170	22969	3124	16243	17867	11959
CN 250	32946	3124	16243	17867	11959
CNO 250	36240	3124	16243	17867	11959
CNB 50	7703	3124		8315	2620
TK 115	6991	1516	2655		
TK 130	10054	1516	4686		3449
TK 175	13519	1516	4686		3449
CM1			1207		
CNP 21/31			1207		
CNM 9,12,16,22,30,36			1207		
CNN 9,12,18,25			1205		
CNN 32,40,50,60			1269		
CNN 70,80,90			1843		
TK 25, 35, 65			1205		
CNB 9, 21, 31, 12				2239	
CNB 16, 22, 30				2347	
- Kod izvedbi "pojačanih" kompleta glavnih kontakata, gore navedene cene se povećavaju za 30%					
- Cene kalema se odnose samo na standardne napone upravljanja					
- Za nestandardne napone cena je 10% veća					
Pomoćni kontakti za UTKN					RSD
CN 10/16					990
CN 25/40					1068
CNM 36-110					5682
CN 63-250					5845