



Prokuplje, Dragoljuba Rakića 7a
+381 27 321 177; +381 27 334 310
Tekući račun: 325-950080000702-77

kontakt@abmelektro.com
www.abmelektro.com
PIB: 100 415 391



RADE KONČAR KONTAKTORI I RELEI D.O.O.



REGULATORI FAKTORA SNAGE

OSNOVNE KARAKTERISTIKE		TIP	RSD
4-stepeni (jednofazni)		RKPFK 4	12064
6-stepeni (jednofazni)		RKPFK 6	15604
8-stepeni (jednofazni)		RKPFK 8	17157
12-stepeni (jednofazni)		RKPFK 12	19503
15-stepeni (trofazni)		RKPFK 15	24388

PRIGUŠNICE

OSNOVNE KARAKTERISTIKE	TIP	RSD
12.5 kVAr/400V 189Hz p=7% (15kVAr/440V)	ERH-7/400/12.5	21347
22.2 kVAr/400V 189Hz p=7% (25kVAr/440V)	ERH-7/400/22.2	30942
44.4 kVAr/400V 189Hz p=7% (50kVAr/440V)	ERH-7/400/44.4	45356

Nazivna nominalna struja Ie kod Un=400 V, AC 6b	Snaga konden. kod Un=400V, AC 6b	Broj pomoćnih kontakata	Dimenzije a x b x c	Težina	Kondenzatorski kontaktori CNNK naizmenični napon upravljanja	Cena
(A)	(kVar)	ukl/fiskl	(mm)	(kg)	Standardni naponi: 230V/50Hz; 400V/50Hz	RSD
18	2,5	1 0	45x71x72,2	0,25	CNNK 2,5	2148
18	5	1 0	45x71x72,2	0,25	CNNK 5	2399
29	7,5	0 0	45x71x72,2	0,275	CNNK 7,5	2617
14	10	2 0	45x72,2x108	0,314	CNNK 10 20	3319
14	10	1 1	45x72,2x108	0,314	CNNK 10 11	3319
18	12,5	2 0	45x72,2x108	0,316	CNNK 12 20	3520
18	12,5	1 1	45x72,2x108	0,316	CNNK 12 11	3520
22	15	2 0	45x72,2x108	0,318	CNNK 15 20	3990
22	15	1 1	45x72,2x108	0,318	CNNK 15 11	3990
29	20	1 0	45x80x121,3	0,333	CNNK 20 10	4190
36	25	1 0	45x80x121,3	0,404	CNNK 25 E 10	5198
36	25	1 0	45x80x121,4	0,404	CNNK 25 10	5534
44	30	1 0	45x80x121,3	0,414	CNNK 30 10	6004
50	40	1 0	55x120x109	0,875	CNNK 40 10	8552
72	50	1 0	55x120x109	0,880	CNNK 50 10	9223
87	60	1 0	55x120x109	0,920	CNNK 60 10	10563
101	70	1 0	70x142x123	1,320	CNNK 70 10	15635
108	75	2 2	130x158x145	2	CNKM 75 22	23442
108	75	2 2	130x158x145	2,47	CNKM 80 22	24313

